

G520

ISO
9001:2008
REGISTERED



VARTECH SYSTEMS INC.

Solutions for Demanding Applications

21" High Resolution Auto Sync Sony Trinitron™ Solution

This solution is intended for the replacement of 20" or 21" Trinitron displays by ABB, HP, Sun, and Foxboro. This 21" FD Trinitron™ CRT is a virtually-flat, high-resolution screen that delivers an outstanding image quality with reduced glare 0.24mm Aperture Grille pitch. It sets a new standard in image clarity and precision Digital Multiscan Technology.

SPECIFICATIONS

FEATURES

- ◆ Auto Sync 30 to 130kHz
- ◆ .24mm Ultra-Fine Dot Pitch
- ◆ Digital Controls with OSD
- ◆ Dual HD15 switchable input
- ◆ 5BNC video input (adapted)
- ◆ Sync on Green Operation

Picture Tube

.24mm Aperture Grille Pitch

Recommended Resolution

1880 x 1440 @ 85Hz

Maximum Resolution

2048 x 1536 @ 75Hz

Scan Frequency

Horizontal: 30 to 130kHz

Vertical: 48 to 170Hz

Active Display Area

15.35"(w) x 11.50"(h)

389.89mm(w) x 292.10mm(h)

On-Screen Display Controls

Brightness, Contrast, and other user controls

Video Input Signal

Analog Video .7V p-p

Sync Input Signal

Separate or Composite Sync: TTL pos. or neg. Sync on Green (SOG) 0.3V p-p neg.

Video Input Connectors

Dual 15 pin HD connectors (switchable)
5 BNC video interface (adapted)

Power Source

90-264 VAC Universal

Line Frequency

50/60Hz

Power Consumption

145 Watts (Maximum)

1W standby; 15W suspend mode

Temperature

Operating: 10 to -40°C

Relative Humidity

Operating 10 to 80%NC

Dimensions

19.7"(w) x 19.6"(h) x 19.1"(d)

500.9mm x 497.84mm x 485.14mm

Weight

67.4 lbs / 28 kg

Warranty

3 Years

Replacement for:

Foxboro GDM20E01

Foxboro GDM20E03

Westinghouse Sun

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com