



## 10.4" Xtreme NEMA 4X Military Grade Panel Mount



The NEMA 4X rated rugged LCD flat panel is adaptable to extreme environments. The display has the ability to withstand harsh ambient environments, has enhanced shock and vibration safeguards as well as Electromagnetic Environmental Interference protection.

The VT104PSSX comes standard with optically bonded chemically strengthened front protective glass for added Shock & Vibration protection and reduced solar reflectivity.

### SPECIFICATIONS

#### FEATURES

- ◆ Bright TFT Display
- ◆ Optically bonded chemically strengthened front protective glass with EMI optional coating
- ◆ Manual Full-Range Dimming to black
- ◆ Conformal Coating of all internal circuit boards
- ◆ Integrated heaters for extended operational temperature capabilities
- ◆ Front or Rear Controls
- ◆ Optional Touch
- ◆ HD15(F), RCA (NTSC/PAL)
- ◆ Sync on Green
- ◆ NEMA 4X Stainless Steel Bezel

\*Supports all VESA standard video formats

#### CONTACT

##### HEADQUARTERS

11529 Sun Belt Ct.  
Baton Rouge, Louisiana 70809

**Phone** 800.223.8050

##### International

001.225.298.0300

**Fax** 225.297.2440

##### E-mail

sales@vartechsystems.com

##### Website

www.vartechsystems.com

#### Display Size

10.4 Inch

#### Panel Type

TFT Active

#### Resolution Capabilities

SVGA

#### Pixel Format

800 x 600

#### Pixel Pitch

.264mm(w) x .264mm (h)

#### Active Display Area

8.315"(w) x 6.236" (h)

211.2mm(w) x 158.4mm(h)

#### Viewing Angle

Left / Right: 70°/70°

Up / Down: 50°/60°

#### Contrast Ratio

500:1 Typical

#### Brightness

400 Nits Typical, with full-range manual dimming

**Optional:** Actively enhanced panel for reliability in high ambient light conditions-

#### Backlight

50,000 Hours Typical

#### Colors Supported

262,144 (optional 16.7M)

#### Input Connectors

HD15(F), RCA (NTSC/PAL),

5 Pin Mini Din (S-Video)

#### Optional:

HD15(M)-5xBNC(F) Interface Cable

#### Video Input

Analog 0.7V p-p/75 ohm

(NTSC/PAL),

#### Sync

TTL Separate H/V

Combined, SOG

#### Power Source

**Connector: Amphenol, Bayonet Mating, Meets MIL-C-5015**

12VDC @ 1.6A

#### Optional:

90-264VAC Universal

24VDC @ 0.50A

18-30VDC

#### Power Consumption

20Watts @+124V

4 Watts Sleep Mode

#### Temperature

Operating: -20 to 50°C

(Optional Operating: -40° C, +55°C)

Storage: -20 to 60°C

#### Humidity

Operating: 10 to 95%NC

Storage: 10 to 95%NC

#### EMI

FCC Part 15 - Class B\*

**Optional:** MIL-STD-461E\*

#### Shock

MIL-STD-901D\*

#### Vibration

MIL-STD-167\*

#### Drip Proof

MIL-STD-810E\*

#### Sand Dust

MIL-STD-810E\*

#### Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

#### Stud Size & Screw Length

10-32 x 1/2"

#### Dimensions

13.2"(w) x 11.2"(h)

335.3mm x 284.5mm

#### Cut Out Dimensions

12.086"(w) x 10.083"(h)

307.0mm x 255.6mm

#### Depth

2.063" / 52.4mm

#### Weight

9.4 lbs / 4.27 kg

#### Bezel Finish

**NEMA 4X:**  
Stainless Steel

#### Touchscreen

#### Optional:

Resistive or Capacitive

#### Touch Interface

Serial

#### Optional:

USB

\*Designed to Meet

### OPTIONS

- 90-264 VAC Universal Power Supply
- 24VDC @ 0.50A
- Resistive or Capacitive Touch
- HD15 to 5BNC Interface Cable

- EMI/RFI conductive ITO coating to of 12 ohms/sq. bonded front protective glass
- Transparent EMI/RFI Micro Mesh for MIL-STD 461E Compliance
- Transparent Heaters for -40°C Operation

[www.vartechsystems.com](http://www.vartechsystems.com)