



10.4" SVGA NEMA 4 Panel Mount LCD Display



This 10.4" flat panel display is a compact design to be placed in a variety of industrial and process control environments requiring a NEMA 4 panel mount SVGA resolution and NTSC/PAL.

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Resistive Touch
- ◆ HD15(F), RCA (NTSC/PAL)
- ◆ Sync on Green
- ◆ SVGA

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

SPECIFICATIONS

Display Size

10.4 Inch

Panel Type

TFT Active

Resolution Capabilities

SVGA (optional XGA)

Pixel Format

800x600 (optional 1024 x 768)

Pixel Pitch

.264mm

Active Display Area

211.2mm(w) x 158.4mm(h)

Viewing Angle

Left / Right: 80°/80° Degrees

Up / Down: 80°/80° Degrees

Contrast Ratio

1000:1 Typical

Brightness

400 Nits Typical (optional 1100 nits)

Colors

16.77M

Response Time

18ms

Input Connector

HD15(F), RCA (NTSC/PAL),
5 Pin Mini Din (S-Video)

Optional:

HD15 to 5BNC Interface Cable

Video Input

Analog 0.7V p-p

Sync

Separate H&V,
Combined, SOG

Power Source

12VDC

Optional:

90-264VAC Universal
24VDC @ 0.50A

Power Consumption

30 Watts

Temperature

Operating: -10° to 50°C

(Optional Operating: -20 to 60°C)

Storage: -20 to 60°C

Humidity

Operating: 10 to 95%NC

Storage: 10 to 95%NC

Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

Stud Size & Screw Length

10-32 x 1/2"

Dimensions

13.2"(w) x 11.2"(h)

335.3mm x 284.5mm

Cut Out Dimensions

12.086"(w) x 10.083"(h)

307.0mm x 255.6mm

Depth

2.063" / 52.4mm

Weight

11 lbs / 5.0 kg

Bezel Finish

NEMA 4:

Black Powder Coat

Cold Rolled Steel

Optional NEMA 4X:

Stainless Steel

Touchscreen

Optional:

Resistive

Touch Interface

Serial

Optional:

USB

OPTIONS

- 90-264 VAC Universal Power Supply
- 24VDC @ 0.50A
- HD15 to 5BNC Interface Cable
- Resistive Touch
- Stainless Steel NEMA 4X Front Panel
- Optical Bonding (VBOND) for added Shock & Vibration protection and/or reduced solar reflectivity
- Armor Touch (must be optically bonded)
- High Brightness 1100 cd/m²
- XGA (1024 x 768) resolution
- -20 to 60°C Operational Temp