



Solutions for Demanding Applications

15.0" XGA DiamondVue Chassis Mount

This 15.0" DiamondVue flat panel display is designed to be placed in a variety of industrial and process control environments requiring a chassis mount that supports VGA to native XGA resolution. This display is auto sync compatible with most PC's video standards and satisfies a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

Display Size

15.0 Inch

Panel Type

TFT Active

Native Resolution

XGA

Native Pixel Format

1024 x 768

Pixel Pitch

.297mm (w) x .297mm (h)

Active Display Area

11.973" (w) x 8.979" (h)
304.12mm (w) x 228.09mm (h)

Viewing Angle

LEFT/RIGHT: 80°/80°
UP/DOWN: 80°/80°

Contrast Ratio

500:1 Typical

Brightness

400 Nits Typical (1950 nits optional)

Back Light

50,000 Hours Typical

Colors Supported

16.7M

Input Connectors

HD15(F), Mini Din 4-way (S-Video), Composite (BNC), DVI

Optional:

HD15(M) to 5xBNC(F) Interface Cable

Video Input

Analog 0.7Vp-p / 75 ohm, Digital, NTSC/PAL

Sync

TTL Separate H&V, Combined, SOG

Power Source

90-264VAC Universal

Optional:

12VDC@ 2.25A

Power Consumption

27 Watts

4 Watts Sleep Mode

Temperature

Operating: 0 to 50°C

Storage: -20 to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 90% NC

Storage: 5 to 95% NC

Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

Dimensions

16.5" (w) x 13.65" (h)

419.1mm(w) x 346.45mm(h)

Depth Behind Panel

2.47"/62.74mm

Stud Size & Screw Length

10-32 x 1/2"

Weight

Unit: 6.5 lbs/2.95kg

Chassis Construction

14 gauge aluminum

Touchscreen

Optional:

Resistive or Capacitive

Touch Interface

USB or Serial

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ XGA Native Resolution
- ◆ Compact, Low Profile
- ◆ HD15(F), Mini Din 4-way (S-Video), Composite (BNC), DVI
- ◆ Wide Viewing Angles
- ◆ Optional Resistive or Capacitive Touch

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Capacitive Touch or Resistive Touch
- 1950 Nits Brightness
- HD15(M) to 5xBNC(F) Interface Cable
- 12VDC Power Supply
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming
- Chemically Strengthened Bonded Overlay on Non-Touch Screen
- 120 to 370 V DC

Marks of Conformity:

FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997

Canada: ICES-003

Australia/New Zealand: AS/NZS CISPR 22

CE

RoHS
WEEE



RoHS
compliant