



15.0" XGA High Bright NEMA 4 (IP65) Chassis Mount LCD

This 15.0" LED Enhanced Sunlight Readable high bright flat panel display is designed to be placed in a variety of outdoor and high ambient light environments requiring a chassis mount that supports VGA to native XGA resolution. This display is auto sync compatible with most PC's video standards and satisfies a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

Display Size

15.0 Inch

Panel Type

LED Enhanced Sunlight Readable Active Matrix TFT Display

Optical Stack Enhancement (OSE)

Unique optical design which boosts efficiency of the backlight's light utilization and minimizes the surface reflection of ambient light. The result is a transmissive enhancement that features higher contrast and a wider range of colors, even in bright outdoor light, than traditional reflective LCDs.

Native Resolution

XGA

Native Pixel Format

1024 x 768

Pixel Pitch

.297mm (w) x .297mm (h)

Optical Bonding

Optical Bonding (VBOND) for added Shock & Vibration protection and/or reduced solar reflectivity

Pixel Pitch

.297mm (w) x .297mm (h)

Active Display Area

11.973"(w) x 8.979"(h)
304.12mm(w) x 228.09mm (h)

Viewing Angle

LEFT/RIGHT: 80°/80°
UP/DOWN: 80°/60°

Contrast Ratio

600:1 Typical

Brightness

1950 Nits Typical, Low-Power, high reliability Solid State LED Backlighting

Back Light

70,000 Hours Typical

Colors Supported

16.7M

Dimming Ratio

1000:1

Input Connectors

HD15(F), Mini Din 4-way (S-Video), Composite (BNC), DVI

Optional:

HD15(M) to 5xBNC(F) Interface Cable

Video Input

Analog 0.7Vp-p / 75 ohm, Digital, NTSC/PAL

Sync

TTL Separate H&V, Combined, SOG

Power Source

90-264VAC Universal

Optional:

12VDC@ 2.25A

Power Consumption

27 Watts
4 Watts Sleep Mode

Temperature

Operating: -10 to 50°C
Storage: -20 to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 95%NC
Storage: 10 to 95%NC

Altitude

Operating: up to 10,000 ft
Storage: up to 40,000 ft

Depth Behind Panel

2.47"/62.74mm

Stud Size & Screw Length

10-32 x 1/2"

Weight

Unit: 7.2 lbs/3.27kg

Chassis Construction

14 gauge aluminum

Touchscreen

Optional:

Resistive or Capacitive

Touch Interface

USB or Serial

FEATURES

- ◆ High Bright 1950 Nit Sunlight Readable Active Matrix TFT Display
- ◆ Low-Power, high reliability Solid State LED Backlighting
- ◆ Optical Bonding (VBOND) for added Shock & Vibration protection and/or reduced solar reflectivity
- ◆ XGA Native Resolution
- ◆ Compact, Low Profile
- ◆ HD15(F), Mini Din 4-way (S-Video), Composite (BNC), DVI
- ◆ Wide Viewing Angles
- ◆ Optional Resistive or Capacitive Touch

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

Marks of Conformity:

FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997
Canada: ICES-003

Australia/New Zealand: AS/NZS CISPR 22 CE

RoHS
WEEE



OPTIONS

- Capacitive Touch or Resistive Touch
- HD15(M) to 5xBNC(F) Interface Cable
- 12VDC Power Supply
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming
- Chemically Strengthened Bonded Overlay on Non-Touch Screen
- 120 to 370 V DC