



15.0" DiamondVue SERIES NEMA 4X Panel Mount LCD



This 15.0" Stainless Steel flat panel display is designed to be placed in a variety of industrial and process control environments requiring a NEMA 4X panel mount that supports VGA to SXGA resolutions* and NTSC/PAL. This display is auto sync compatible with most PC's video standards and satisfies a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Compact, Low Profile
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Resistive or Capacitive Touch
- ◆ HD15(F), RCA (NTSC/PAL), DVI & 5 Pin Mini Din (S Video)

Display Size

15.0 Inch

Panel Type

TFT Active

Resolution Capabilities

VGA to SXGA*

Pixel Format

640 x 480, 800 x 600,
1024 x 768, 1280 x 1024

Pixel Pitch

.297mm (w) x .297mm (h)

Active Display Area

11.973"(w) x 8.979"(h)
304.12mm(w) x 228.09mm (h)

Viewing Angle

Left / Right: 70°/70°
Up / Down: 60°/65°

Contrast Ratio

300:1 Typical

Brightness

450 Nits Typical

Back Light

50,000 Hours Typical

Colors Supported

16.7M

Input Connectors

HD15(F), RCA (NTSC/PAL),
5 Pin Mini Din (S-Video), DVI

Optional:

HD15(M) to 5xBNC(F) Interface
Cable

Video Input

Analog 0.7V p-p,/ 75 ohm, Digital
Sync: TTL Separate H&V
Combined, SOG

Power Source

90-264VAC Universal

Optional:

12VDC or 24VDC

Power Consumption

27 Watts @ 115 VAC
4 Watts Sleep Mode

Temperature

Operating: 0 to 50°C
Storage: -20 to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 95%NC
Storage: 10 to 95%NC

Altitude

Operating: up to 10,000 ft
Storage: up to 40,000 ft

Cut Out Dimension

15.06"(w) x 12.2"(h)
382.52mm(w) x 309.88mm(h)

Depth Behind Panel

2.57" / 65.2mm

Stud Size & Screw Length

10-32 x 1/2"

Weight

Unit: 14.8 lbs / 6.73 kg
Shipping: 30 lbs / 13.64 kg

Chassis Construction

16 gauge Stainless Steel

Bezel Finish

NEMA 4X:

Stainless Steel

Touchscreen

Optional:

Resistive or Capacitive or
Armor Touch (must optically bond)

Touch Interface

Serial

Optional:

USB

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Capacitive or Resistive Touch
- Armor Touch Rugged Touch Screen (must have optical bond)
- HD15 to 5BNC Interface Cable
- 12VDC Power Supply
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming