



15.0" XGA Wall / Arm Mount



This 15.0" flat panel wall mount display is designed to be placed in a variety of industrial and process control environments requiring arm mounting that supports VGA to XGA resolutions* and NTSC/PAL. This display is auto sync compatible with most PC's video standards and satisfies a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Compact Design
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Resistive or Capacitive Touch
- ◆ HD15(F)

Display Size

15.0 Inch

Panel Type

TFT Active

Resolution Capabilities

VGA to XGA*

Pixel Format

640 x 480, 800 x 600,
1024 x 768

Pixel Pitch

.297mm (w) x .297mm (h)

Active Display Area

12.046"(w) x 9.050"(h)
305.97mm (w) x 229.87mm (h)

Viewing Angle

Left / Right: 70°/70°
Up / Down: 60°/65°

Contrast Ratio

300:1 Typical

Brightness

450 Nits Typical

Back Light

50,000 Hours Typical

Colors Supported

16.2M

Input Connectors

HD15(F), RCA (NTSC/PAL)
5 Pin Mini Din (S-Video)

Optional:

HD15(M) to 5xBNC(F) Interface
Cable

Video Input

Analog 0.7Vp-p / 75 ohm, Digital,
NTSC/PAL

Sync

TTL Separate H&V,
Combined, SOG

Power Source

90-264VAC Universal

Optional:

12VDC@ 2.25A

Power Consumption

27 Watts

4 Watts Sleep Mode

Temperature

Operating: 0 to 50°C

Storage: -20 to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 90% NC

Storage: 5 to 95% NC

Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

Outside Enclosure Dimension

15.312"(w) x 12.00"(h)

388.92mm(w) x 304.80mm(h)

Depth Behind Panel

2.435" / 61.84mm nominal

Weight

10.4 lb

Chassis Construction

Integrated welded construction

Bezel Finish

Black Powder Coat Aluminum

Touch screen

Optional:

Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

Shipping Weight and Dimensions

Boxed: 24 lbs

Box: 24" x 21" x 12"

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Resistive or Capacitive Touch
- 12VDC Power Supply
- HD15(M) to 5xBNC(F) Interface Cable
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming