



15.0" NEMA 4X Enclosed Wall Mount Display System



This 15.0" NEMA 4X Stainless Steel flat panel enclosed wall mount display is designed to be placed in a variety of industrial and process control environments requiring wall mounting that supports VGA to SXGA resolutions*. This display is auto sync compatible with most PC's video standards and satisfies a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Compact Design
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Resistive or Capacitive Touch
- ◆ HD15(F), NTSC/PAL & S Video, DVI
- ◆ NEMA 4X Stainless Steel Enclosure

<p>Display Size 15.0 Inch</p> <p>Panel Type TFT Active</p> <p>Resolution Capabilities VGA to SXGA*</p> <p>Pixel Format 640 x 480, 800 x 600 1024 x 768, 1280 x 1024*</p> <p>Active Display Area 11.97"(w) x 8.98(h) 304mm(w) x 228mm(h)</p> <p>Viewing Angle Left / Right: 70/70 Degrees Up / Down: 70/70 Degrees</p> <p>Contrast Ratio 300:1 Typical</p> <p>Brightness 450 Nits Typical</p> <p>Back Light 50,000 Hours Half Life</p> <p>Colors Supported 16M</p> <p>Input Connector Video: HD15(F) NTSC/PAL: RCA jack & mini din S Video</p> <p>Video Input Analog 0.7V p-p</p> <p>Sync Separate H&V, Composite and SOG</p> <p>Power Source 12VDC Optional: 115/220VAC Power Supply</p>	<p>24VDC Power Supply</p> <p>Temperature Operating: 0 to 50°C Storage: -20 to 60°C</p> <p>Humidity Operating: 10 to 95%NC Storage: 10 to 95%NC</p> <p>Altitude Operating: up to 10,000 ft Storage: up to 40,000 ft</p> <p>Power Consumption 35 Watts Maximum</p> <p>Enclosure Dimensions 18.44"(w) x 15.64"(h) 468.38mm(w) x 397.26mm(h)</p> <p>Depth 2.16" / 54.8mm nominal</p> <p>Chassis Construction Integrated welded construction</p> <p>Bezel Finish NEMA 4X: Stainless Steel Bezel</p> <p>Touchscreen Optional: Resistive or Capacitive</p> <p>Touch Interface Serial or USB</p> <p>Weight 33.4 lbs/ 15.18 kg</p>
---	--

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Resistive Touch
- Capacitive Touch
- 115/220VAC Power Supply
- 24VDC Power Supply

www.vartechsystems.com