



Solutions for Demanding Applications

17.0" Tabletop LCD Flat Panel Display

This 17.0" flat panel display is a compact design to be placed in a variety of industrial and process control environments requiring resolutions from VGA to SXGA*. These displays are auto-sync compatible with PC's video standards and satisfy a wide variety of industrial control and man-machine interface applications and are available in a variety of sizes.



SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ High Contrast Ratio
- ◆ Low Power Consumption
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Touch Systems

Display Size

17.0 Inch

Panel Type

TFT Active

Resolution Capabilities

VGA to SXGA*

Pixel Format
640 x 480, 800 x 600,
1024 x 768, 1280 x 1024*
Pixel Pitch

.264mm (w) x .264mm (h)

Viewing Angle

Left / Right: 89°/89°

Up / Down: 89°/89°

Active Display Area
13.304" (w) x 10.643" (h)
337.920mm (w) x 270.336mm (h)
Contrast Ratio

600:1 Typical

Brightness

250 Nits

Backlight

50,000 Hours Typical

Colors Supported

16.7M

Video Input

0.7Vp-p / 75 ohm, Digital

Sync

TTL Separate H&V

Combined, SOG

Video Input Connector
HD15(F), DVI-D, RCA (NTSC/PAL),
5 Pin Mini Din (S-Video)
Optional:

HD15(M) to 5xBNC(F) Interface Cable

Power Source

90-264VAC Universal

Optional:

12VDC @ 2.5A

Power Consumption

35 Watts @ 115VAC

4 Watts Sleep Mode

Temperature

Operating: 0 to 50° C

Storage: -20 to 60° C

Optional:

Operating: -20°C or -40°C

Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

Touchscreen
Optional:

Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

 11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Capacitive or Resistive Touch
- HD15(M) to 5xBNC(F) Interface Cable
- 12VDC @ 2.5A
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming

Marks of Conformity:

 FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR
22:2005, CISPR 24:1997

Canada: ICES-003

Australia/New Zealand: AS/NZS CISPR 22

CE

RoHS

WEEE

