



17.0" SXGA NEMA 4X High Bright Panel Mount



This 17.0" NEMA 4x stainless steel flat panel display is a compact design to be placed in a variety of industrial and process control environments requiring resolutions from VGA to SXGA*. These displays are auto sync compatible with PC's video standards and satisfy a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ HD15(F), DVI-D Pin, RCA, Mini Din
- ◆ High Contrast Ratio
- ◆ Low Power Consumption
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Touch Systems
- ◆ VGA to SXGA Resolution

Display Size

17.0 Inch

Panel Type

TFT Active

Resolution Capabilities

VGA to SXGA*

Pixel Format

640 x 480, 800 x 600,
1024 x 768, 1280 x 1024*

Pixel Pitch

.264mm (w) x .264mm (h)

Viewing Angle

Left / Right: 80°/80°

Up / Down: 80°/80°

Active Display Area

13.304" (w) x 10.643" (h)
337.920mm (w) x 270.336mm (h)

Contrast Ratio

500:1 Typical

Brightness

1200 Nits

Backlight

30,000 Hours Typical

Colors Supported

262K (RGB 6-bit data)

Video Input

0.7Vp-p / 75 ohm, Digital

Sync

TTL Separate H&V

Combined, SOG

Video Input Connector

HD15(F), DVI-D, RCA (NTSC/PAL),

5 Pin Mini Din (S-Video)

Optional:

HD15(M) to 5xBNC(F) Interface Cable

Power Source

90-264VAC Universal

Optional:

12VDC @ 4.8A

Power Consumption

60 Watts @ 115VAC

10 Watts Sleep Mode

Temperature

Operating: 0 to 50° C

Storage: -20 to 60° C

Optional:

Operating: -20° C or -40° C

Humidity

Operating: 8 to 95% NC

Storage: 8 to 95% NC

Altitude

Operating: up to 10,000 ft

Storage: up to 30,000 ft

Chassis Construction

18 gauge Stainless Steel

Bezel Finish

NEMA 4X Stainless Steel

Touchscreen

Optional:

Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

Weight

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Capacitive or Resistive Touch
- HD15(M) to 5xBNC(F) Interface Cable
- 12VDC @ 2.5A
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20° C
- Transparent Thermal Heaters for -40° C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming

www.vartechsystems.com