



17.0" AutoSync Low Scan Rugged Rack Mount (8U) LCD



The VT170R1 Rack Mount (8U) LCD has been designed primarily for Low Scan Legacy Systems as replacements for CRT monitors. They utilize a modern SXGA TFT (1280 x 1024* pixels) panel and a versatile Analog-Digital interface board. All elements have been packaged in a compact metal.

By special development of their own Signal Recognition and Scaling software, and access to an extensive library of older signal timings gained from 25 plus years of CRT monitor manufacturing, VarTech has created a Multiscan ("Universal:") flat panel monitor with unique 15kHz to 64kHz display capabilities. Signal timings are factory preset and added to the Program Store by customer request.

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Protective Faceplate
- ◆ Specially designed for Low Scan Signals
- ◆ Automatic Image Size Adjustment
- ◆ TTL, Analog & Interlaced Signals accepted
- ◆ Rugged Metal Construction with Good Stability

SPECIFICATIONS

Display Size

17.0 Inch

Panel Type

TFT Active

Resolution Capabilities

CGA, EGA 640 x 480 to 1280 x 1024*

Scan Frequency

Horizontal: 15.625-64kHz

Vertical: 50-75Hz

Pixel Pitch

.264 mm

Active Display Area

13.304" (w) x 10.643" (h)

337.920mm (w) x 270.336mm (h)

Viewing Angle

Left / Right: 89/89 Degrees

Up / Down: 89/89 Degrees

Contrast Ratio

1000:1 Typical

Brightness

280 Nits Typical

Back Light

50,000 Hours Half Life

Front User Controls

5 Position Membrane OSD

Colors Displayed

16.7 M (8-bit)

Video Input

Analog RGB 0.7-1.0V p-p or

TTL > 2.75V p-p

Sync:

Separate H&V (±ve) TTL or

Composite (-ve) TTL or

Sync on Green (-ve) 0.3V

Video Input Connector:

HD15(F), 5BNC and D9

Power Source

90-264VAC Universal

Optional: 12VDC @ 2.5 A

Temperature

Operating: 0 to 50° C

Storage: -20 to 60° C

Optional Operating Temp:

-20 to +50C

Humidity

Operating : 10 to 95% NC

Storage: 10 to 95% NC

Altitude

Operating : up to 10,000 ft

Storage: up to 40,000 ft

Power Consumption

50 Watts @ 115 VAC

4 watts sleep mode

Dimensions

16.250"(w) x 13.588"(h)

412.75mm x 345.14mm

Case Finish

Black Powder Coated

Rack Mount

8U

Touch Screens

Resistive

Capacitive

Touch Interface

Serial

Optional: USB

Shipping Information

Unit: 20.2 lbs

Boxed: 29 lbs

*Supports all VESA standard video formats

Marks of Conformity:

FCC47 CFR part 15, subpart B

EMC: EN 55022:2006, EN

55024:1998, CISPR 22:2005,

CISPR 24:1997

Canada: ICES-003

Australia/New Zealand: AS/

NZS CISPR 22

CE

RoHS

WEEE



CONTACT

HEADQUARTERS

11529 Sun Belt Ct.

Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

◆ Capacitive Touch or Resistive Touch with Serial or USB

◆ +12VDC

◆ Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity

◆ Integrated Heaters & Thermostat for extended Operational Temperature, -20 to +50C

◆ Automatic Dimming Sensor

◆ Manual Full-Range Dimming