

# VT170VR

ISO  
9001:2008  
REGISTERED



**VARTECH**  
SYSTEMS INC.

Solutions for Demanding Applications

## VT170VR NEMA 4 (IP65) Fully Enclosed LCD

Fully Enclosed NEMA 4 (IP65) LCD displays are an ideal HMI solution complete with standard resistive touch. These small footprint fully sealed LCDs are ideal in a variety of harsh environment manufacturing facilities.



### SPECIFICATIONS

**Display**

17" SXGA TFT LCD

**Resolution**

1280 x 1024

**Viewing Angle**

160° (H) / 160° (V)

**Pixel Pitch**

0.264mm

**Display Colors**

16.7M

**Brightness**

300 cd/m<sup>2</sup>

**Contrast Ratio**

800:1

**Response Time**

5 ms

**Power Input**

100-240 VAC 1.5A 50/60 Hz

**Optional:**

12/24V DC,  
6 to 32V DC

**Connections**

Sealed connections for VGA, Touch, and Power

**Temperature**

Operational: -10° to 60°C

Storage: -20° to 65°C

**Humidity**

Operational: 0 to 90% RH NC

Storage: 5 to 95% RH NC

**Touch Screen**

Resistive Standard

**Construction**

Fully Enclosed, NEMA 4 (IP65) Black  
Powder Coated Aluminum, Gasketed

**Dimensions:**

17.26" (W) x 17.59" (H) x 3.90" (D)

### FEATURES

- ◆ Rear Exit Cable Connectors
- ◆ Fully Enclosed NEMA 4 (IP65) Enclosure
- ◆ Resistive Touch Screen
- ◆ Sealed Connections for VGA, Touch, and Power

### CONTACT

**HEADQUARTERS**

11529 Sun Belt Ct.  
Baton Rouge, Louisiana 70809

**Phone** 800.223.8050

**International**

001.225.298.0300

**Fax** 225.297.2440

**E-mail**

sales@vartechsystems.com

**Website**

www.vartechsystems.com

### OPTIONS

- 12/24V DC Power
- 6 to 32V DC Power

**Marks of Conformity:**

FCC47 CFR part 15, subpart B  
EMC: EN 55022:2006, EN 55024:1998, CISPR  
22:2005, CISPR 24:1997

Canada: ICES-003

Australia/New Zealand: AS/NZS CISPR 22

CE

RoHS

WEEE



**Specs subject to change without notice. Please inquire before ordering.**