



Solutions for Demanding Applications

## 17.0" NEMA 4X (IP66) WORKSTATION, WIDE OPERATIONAL TEMPERATURE CAPABILITY

This 17.0" workstation is designed to be placed in a variety of food/beverage processing, pharmaceutical and process control environments requiring a NEMA 4X workstation. The display supports VGA to SXGA resolutions\*. The enclosure has a NEMA 4X tactile keyboard and pointing device.

### SPECIFICATIONS

### FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Closed-Loop thermal management system
- ◆ HD15(F), RCA (NTSC/PAL), 5 Pin Mini Din (S-Video), DVI
- ◆ VGA to SXGA Resolution
- ◆ 110 / 220 VAC Power
- ◆ Optional Touch Systems: Resistive and Capacitive
- ◆ Optional Power Supply: 12VDC or 24VDC
- ◆ Solid Stainless Steel construction
- ◆ Water tight Rox Gland for cable exit & entry
- ◆ Wall, Bulkhead, Pole, Pedestal Mount

#### Display

17.0 Inch - TFT Active

#### Resolution Capabilities

VGA to SXGA\*

#### Pixel Format

640 x 480, 800 x 600, 1024 x 768, 1280 x 1024\*

#### Active Display Area

13.304"(w) x 10.643"(h)  
337.920mm(w) x 270.336mm(h)

#### Viewing Angle

L / R: 89°/89° Up / Down: 89°/89°

#### Contrast Ratio

600:1 Typical

#### Brightness

250 Nits Typical

#### Back Light

50,000 Hours Half Life

#### Colors Supported

16.8M

#### Power Source

90-264VAC (Optional 12VDC or 24 VDC)

#### Input Connector

HD15(F), RCA (NTSC/PAL), S-VIDEO, DVI

#### Video Input

Analog 0.7V p-p, NTSC/PAL

#### Sync

Separate H&V, Combined, SOG

#### Temperature

Operating: 0° to 50°C (optional -20°C)

Storage: -20° to 60°C

#### Humidity

Operating / Storage: 10 to 95%NC

#### Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

#### Enclosure Dimension

22"(w) x 28"(h)

558.80(w) x 711.20(h)

#### Depth Behind Panel

8.9415" / 227.10mm

#### Chassis Construction

16 gauge Stainless Steel

14 gauge Large Cabinet

#### Keyboard / Pointer

114 Key Tactile Membrane / Touchpad

#### Touch screen (optional)

Resistive OR Capacitive

#### Touch Interface

Serial (Optional USB)

### COMPUTER SPECIFICATIONS

#### Processor

T4500 2.30 GHz 800MHz FSB Intel Dual Core

#### BIOS

Phoenix-Award 16Mbit (SPI) with RPL/PXE LAN Boot ROM, SmartView and customer CMOS backup

#### O/S

Microsoft XP Professional (optional Windows XP Embedded)

#### System Memory

2 DDR2 533/667 SDRAM sockets, 2GB standard, 4GB optional (~3.25 recognizable)

#### Chip Set

Intel® GME965+ICH8M/EM

#### VGA

Intel® GME965 GMCH Gen4 integrated graphics engine

#### Hard Drive

320GB Fast Access SATA drive

#### Power Input

100-240VAC 1.5A 50/60 HZ

#### I/O Ports

2 RS-232 COM port (Optional RS-422\485 port)  
2 LAN ports  
6 USB 2.0  
2 Audio jacks

#### Firewire Ports

2 x IEEE 1394a

#### DVD Drive (E-IDE / ATAPI)

DVD-R, DVD+R, DVD-RW, DVD+RW, DVD-R DL, DVD+R9, CD-R, CD-RW

#### Marks of Conformity:

FCC47 CFR part 15, subpart B  
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997  
Canada: ICES-003  
Australia/New Zealand: AS/NZS CISPR 22  
CE  
RoHS  
WEEE



\*Supports all VESA standard video formats

### CONTACT

#### HEADQUARTERS

11529 Sun Belt Ct.  
Baton Rouge, Louisiana 70809

Phone 800.223.8050

#### International

001.225.298.0300

Fax 225.297.2440

#### E-mail

sales@vartechsystems.com

#### Website

www.vartechsystems.com

### OPTIONS

- **Internal (Inside Enclosure)**  
No Computer or Customer Provided Computer
- **Alternate Keyboards Available**
- **-20°C Operational Temperatures**
- **Resistive or Capacitive Touch Screen**
- **Remote (up to 3000' away) with KVM extender**  
PC up to 500' away with CAT5 KVM  
PC up to 3000' away with fiber optic KVM
- **Windows XP Embedded**