



19.0" AutoSync Low Scan Rugged Tabletop Flat Panel Monitor w/ Infra red Touchscreen



The VT190M1-IR with Infra-red touchscreen has been designed primarily for Low Scan Legacy Systems as replacements for 20"/21" CRT monitors. They utilize a modern SXGA TFT (1280 x 1024 pixels) panel and a versatile Analog-Digital interface board. All elements have been packaged in a compact metal housing and attached to a heavy-duty stand. With the VESA mount, the display can be attached to a retractable arm or a fixed resident post.

By special development of their own Signal Recognition and Scaling software, and access to an extensive library of older signal timings gained from 25 plus years of CRT monitor manufacturing, VarTech has created a Multiscan ("Universal:") flat panel monitor with unique 15.625-64kHz display capabilities. Signal timings are factory preset and added to the Program Store by customer request.

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Protective Faceplate
- ◆ High Brightness and Wide Viewing Angles
- ◆ Specially designed for Low Scan Signals
- ◆ Automatic Image Size Adjustment
- ◆ TTL, Analog & Interlaced Signals accepted
- ◆ Rugged Metal Construction with Good Stability
- ◆ Infra-red Touchscreen

SPECIFICATIONS

Display Size

19.0 Inch TFT Active

Panel Type

TFT Active

Resolution Capabilities

CGA, EGA 640 x 480 to 1280 x 1024

Scan Frequency

Horizontal: 15.625-64kHz

Vertical: 50-75Hz

Pixel Pitch

.297 mm

Active Display Area

14.82" x 11.85"

376.32mm x 301.06mm

Viewing Angle

Left / Right: 85/85 Degrees

Up / Down: 85/85 Degrees

Contrast Ratio

500:1

Brightness

250 Nits Typical

Back Light

50,000Hours Half Life

Front User Controls

5 Position Membrane OSD

Colors Displayed

16M

Video Input

Analog RGB 0.7-1.0V p-p orTTL>2.75V

p-p

Sync:

Separate H&V (±ve) TTL or

Composite (-ve) TTL or

Sync on Green (-ve) 0.3V

Video Input Connector:

HD15(F), 5BNC and D9

Power Source

90-264VAC Universal

Temperature

Operating: 0 to 50° C

Storage: -20 to 60° C

Optional:

Operating: -20° to 55° C

Humidity

Operating : 10 to 95% NC

Storage: 10 to 95% NC

Altitude

Operating : up to 10,000 ft

Storage: up to 40,000 ft

Power Consumption

50 Watts

Dimensions

17.750"(w) x 15.250"(h)

450.9mm x 387.35mm

Depth

3.189" / 81mm

Weight

54 lbs

Chassis Construction

16 gauge Stainless Steel

Case Finish

Black Powder Coated

Touch Screens

Resistive

Capacitive

Touch Interface

Serial

Optional:

USB

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- +12VDC
- Resistive & Capacitive Touch w/ Serial or USB
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature, -20 to +50C
- Automatic Dimming Sensor
- Manual Full-Range Dimming

www.vartechsystems.com