



19.0" NEMA 4X Military Grade Panel Mount



The NEMA 4X rated rugged LCD flat panel is adaptable to extreme environments. The display has the ability to withstand harsh ambient environments, has enhanced shock and vibration safeguards as well as Electromagnetic Environmental Interference protection.

The VT190PSSX comes standard with optically bonded chemically strengthened front protective glass for added Shock & Vibration protection and reduced solar reflectivity.

SPECIFICATIONS

FEATURES

- ◆ Bright TFT Display
- ◆ Optically bonded laminated chemically strengthened front protective glass with optional EMI coating
- ◆ Manual Full-Range Dimming
- ◆ Conformal Coating of all internal circuit boards
- ◆ Integrated heaters for extended operational temperature capabilities
- ◆ Front or Rear Controls
- ◆ Drop in Replacement for 18.1"

Marks of Conformity:

FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997
Canada: ICES-003
Australia/New Zealand: AS/NZS CISPR 22
CE
RoHS
WEEE



Display Size

19.0 Inch

Panel Type

TFT Active

Resolution Capabilities

VGA to SXGA

Pixel Format

640 x 480, 800 x 600,
1024 x 768, 1280 x 1024*

Pixel Pitch

.294mm (w) x .294mm (h)

Viewing Angle

Left / Right: 89°/89°
Up / Down: 89°/89°

Active Display Area

14.82" (w) x 11.85" (h)
376.32mm x 301.06

Contrast Ratio

500:1

Brightness

250 Nits, with full-range manual dimming

Optional: Actively enhanced panel for reliability in high ambient light conditions

Backlight

50,000 Hrs Typical

Colors Supported

16.8M

Video Input

Analog 0.7V p-p/ 75ohm, Digital

Sync

TTL Separate H&V
Combined, SOG

Input Connectors

HD15(F), DVI-D,
RCA, Mini-Din (S-Video)

Optional:

HD15(M) to 5xBNC(F) Interface Cable

Power Source

**Connector: Amphenol, Bayonet Mating,
Meets MIL-C-5015**

+12VDC@2.5a

Optional:

110/220 VAC
+24VDC
18-30VDC

Power Consumption

35 Watts@ 115VAC
8 Watts Sleep Mode

Temperature

Operating: -20 to 50° C
(Optional Operating: -40° C, +55° C)
Storage: -20 to 60° C

EMI

FCC Part 15 - Class B*
Optional: MIL-STD-461E*

Shock

MIL-STD-901D*

Vibration

MIL-STD-167*

Drip Proof

MIL-STD-810E*

Sand Dust

MIL-STD-810E*

Altitude

Operating: up to 10,000 ft
Storage: up to 40,000 ft

Humidity

Operating: 10 to 95% NC
Storage: 10 to 95% NC

Chassis Construction

18 gauge Stainless Steel

Cutout Dimension

17.862"(w) x 14.582(h)
453.7mm x 370.4mm

Bezel Finish

NEMA 4X Stainless Steel

Touchscreen

Optional:
Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

Weight

23.6 lbs/ 10.73 kg

*Designed to Meet

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Capacitive Touch
- Resistive Touch
- HD15 to 5BNC adapter cable
- EMI/RFI conductive ITO coating to of 12 ohms/sq. bonded front protective glass
- Transparent EMI/RFI Micro Mesh for MIL-STD 461E Compliance
- Transparent Heaters for -40C Operation
- Automatic Dimming Sensor