



19.0" AutoSync Low Scan Rack Mount Flat Panel



The VT190R1 has been designed primarily for Low Scan Legacy Systems as replacements for 20"/21" CRT monitors. All elements have been packaged in a compact 9U rack mountable metal housing. An optional 1U filler plate can be provided to accommodate 10U replacement displays.

By special development of their own Signal Recognition and Scaling software, and access to an extensive library of older signal timings gained from 25 plus years of CRT monitor manufacturing, VarTech has created a Multiscan "Universal" flat panel monitor with unique 15.625-64kHz display capabilities.

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Protective Faceplate
- ◆ High Brightness and Wide Viewing Angles
- ◆ Specially designed for Low Scan Signals
- ◆ Automatic Image Size Adjustment
- ◆ TTL, Analog & Interlaced Signals accepted
- ◆ Rugged Metal Construction

Marks of Conformity:

FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997
Canada: ICES-003
Australia/New Zealand: AS/NZS CISPR 22

CE
RoHS
WEEE



SPECIFICATIONS

Display Size

19.0 Inch TFT Active

Panel Type

TFT Active

Resolution Capabilities

CGA, EGA 640 x 480 to 1280 x 1024

Scan Frequency

Horizontal: 15.625-64kHz
Vertical: 50-75Hz

Pixel Pitch

.098(h) x .294(v)

Active Display Area

14.82" x 11.85"
376.32mm x 301.06mm

Viewing Angle

Left / Right: 85°/85°
Up / Down: 85°/85°

Contrast Ratio

500:1

Brightness

250 Nits Typical

Back Light

50,000Hours Half Life

Front User Controls

5 Position Membrane OSD

Colors Displayed

16M

Video Input

Analog RGB 0.7-1.0V p-p orTTL>2.75V p-p

Sync:

Separate H&V (±ve) TTL or Composite (-ve) TTL or Sync on Green (-ve) 0.3V

Video Input Connector:

HD15(F), 5BNC and D9

Power Source

90-264VAC Universal

Temperature

Operating: 0 to 50° C
Storage: -20 to 60° C

Optional:

Operating: -20°C or -40°C

Humidity

Operating : 10 to 95% NC
Storage: 10 to 95% NC

Altitude

Operating : up to 10,000 ft
Storage: up to 40,000 ft

Power Consumption

50 Watts

Dimensions

18.98"(w) x 15.72"(h)
482.1mm x 399.3mm

Depth

3.27" / 83 mm

Weight

30 lbs (approximate)

Chassis Construction

16 gauge Stainless Steel

Case Finish

Black Powder Coated

Touch Screens

Resistive
Capacitive

Touch Interface

Serial

Optional

USB

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Resistive or Capacitive Touch w/ Serial or USB
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming