



19.0" VBOND SXGA Rack Mount Flat Panel



VarTech Systems unique VBOND process seals either a top cover glass or touch screen directly to the face of the display bezel. This bonding process eliminates the air-gap between the display and the cover glass, vastly reducing reflective light, which causes visual washout of the display image. VBOND also enhances structural integrity by supporting the LCD assembly with the cover glass. The bond maintains perfect display uniformity while providing shock protection and elimination of fogging caused by trapped moisture accumulating in typical air gap assemblies.

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ VBOND enhanced LCD screen
- ◆ Anti-Reflective Protective Faceplate
- ◆ Digital, Analog, and NTSC Inputs
- ◆ High Contrast Ratio
- ◆ Optional Touch Systems
- ◆ HD15(F), DVI-D Pin, RCA, Mini Din
- ◆ VGA to SXGA

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

SPECIFICATIONS

Display Size

19.0 Inch

Panel Type

TFT Active

Resolution Capabilities

VGA to SXGA

Pixel Format

640 x 480, 800 x 600,
1024 x 768, 1280 x 1024*

Pixel Pitch

.294mm (w) x .294mm (h)

Viewing Angle

Left / Right: 89°/89°

Up / Down: 89°/89°

Active Display Area

14.82" (w) x 11.85" (h)

376.32mm x 301.06

Contrast Ratio

500:1

Brightness

250 Nits

Backlight

50,000 Hrs Typical

Colors Supported

16.8M

Video Input

Analog 0.7V p-p/ 75ohm, Digital

Sync

TTL Separate H&V

Combined, SOG

Input Connectors

HD15(F), DVI-D Pin,

RCA, Mini-Din (S-Video)

Optional:

HD15(M) to 5xBNC(F) Interface Cable

Power Source

90-264VAC Universal

Optional:

+12VDC@2.5a

+24VDC

Power Consumption

35 Watts@ 115VAC

8 Watts Sleep Mode

Temperature

Operating: 0 to 50° C

Storage: -20 to 60° C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 95% NC

Storage: 10 to 95% NC

Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

Chassis Construction

18 gauge Stainless Steel

Bezel Finish

Black Powder Coat

Cold Rolled Steel

Touchscreen

Optional:

Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

Dimensions

18.98"(w) x 15.72" (h)

482.2mm x 399.3

Depth

3.25" / 82.6

Weight

24 lbs/ 10.91 kg

OPTIONS

- Capacitive or Resistive Touch
- HD15 to 5BNC adapter cable
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming