



20.1" UXGA Transflective Chassis Mount LCD



This 20.1" Transflective LCD display is designed to be placed in a variety of applications where the panel will be exposed to indirect sunlight. Transflective displays reflect the light eliminating the need for additional expensive backlights and brightens the screen in indirect sunlight without increasing power consumption. These displays are auto sync compatible with PC's video standards and satisfy a wide variety of industrial control and man-machine interface applications and are available in a variety of sizes.

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ VGA to UXGA Resolution Capabilities*
- ◆ Picture in Picture
- ◆ Anti-Reflective Protective Faceplate
- ◆ HD15(F), DVI-I29 Pin, RCA, Mini Din
- ◆ Film Enhanced for Indirect Sunlight Readability

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

SPECIFICATIONS

Display Size

20.1 Inch

Panel Type

TFT Active

Resolution

VGA to UXGA*

Pixel Format

640 x 480, 800 x 600, 1024 x 768
1280 x 1024, 1600 x 1200*

Pixel Pitch

.255mm (w) x .255mm (h)

Viewing Angle

Left / Right: 85°/85°

Up / Down: 85°/85°

Active Display Area

16.062"(w) x 12.047"(h)
408.00mm x 306.00mm

Picture in Picture

Small Window: 3.6" (w) x 2.9" (h)

Med Window: 5.0" (w) x 9" (h)

Large Window: 6.5" (w) x 5.0" (h)

Contrast Ratio

400:1

Colors Supported

16.8M

Brightness

Film Enhanced for Indirect
Sunlight Readability

Backlight

50,000 hrs typical

Video Input

0.7Vp-p / 75 ohm Digital

Sync

TTL Separate H&V,
Combined, SOG

Input Connectors

HD15(F), DVI-I29 Pin,
(NTSC / PAL)

5 PIN MINI-DIN (S-Video)

Optional:

HD15(M) - 5xBNC(F) Interface Cable

Power Source

90-264VAC Universal

Optional:

24VDC @ 2.8A

Power Consumption

50 Watts @115VAC

8 Watts Sleep Mode

Temperature

Operating: 0 to 50°C

Storage: -20 to 60°C

Humidity

Operating: 10 to 95%NC

Storage: 10 to 95 NC

Storage: -20 to 60°C

Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

Response Time

T_R = 9ms typical (22 max)

T_F = 7ms typical (23 max)

Rear Chassis Construction

16 gauge Stainless Steel

TouchScreen

Optional:

Capacitive

OPTIONS

- Capacitive Touchscreen
- HD15 to 5BNC Adapter
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature, 20 to +50C
- Automatic Dimming Sensor
- Manual Full-Range Dimming