



20.1" VBOND UXGA Rack Mount Flat Panel



VarTech Systems unique VBOND process seals either a top cover glass or touch screen directly to the face of the display bezel. This bonding process eliminates the air-gap between the display and the cover glass, vastly reducing reflective light, which causes visual washout of the display image. VBOND also enhances structural integrity by supporting the LCD assembly with the cover glass. The bond maintains perfect display uniformity while providing shock protection and elimination of fogging caused by trapped moisture accumulating in typical air gap assemblies.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ VBOND enhanced LCD screen
- ◆ Anti-Reflective Protective Faceplate
- ◆ Digital, Analog, and NTSC Inputs
- ◆ Picture in Picture
- ◆ Optional Capacitive or Resistive Touch
- ◆ Optional Resident 5BNC
- ◆ HD15(F), DVI-D Pin, RCA, Mini Din

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

Display Size

20.1 Inch

Panel Type

TFT Active

Resolution

VGA to UXGA*

Pixel Format

640 x 480, 800 x 600, 1024 x 768
1280 x 1024, 1600 x 1200*

Pixel Pitch

.255mm (w) x .255mm (h)

Viewing Angle

Left / Right: 178°/178°
Up / Down: 178°/178°

Active Display Area

16.062"(w) x 12.047"(h)
408.00mm x 306.00mm

Picture in Picture

Small Window: 3.6" (w) x 2.9" (h)
Med Window: 5.0" (w) x 4.9" (h)
Large Window: 6.5" (w) x 5.0" (h)

Contrast Ratio

900:1

Brightness

300 Nits Typical

Colors Supported

16.8M

Backlight

50,000 Hrs Typical

Video Input

0.7Vp-p / 75 ohm Digital

Sync

TTL Separate H&V,
Combined, SOG

Input Connectors

HD15(F), DVI-D Pin, (NTSC / PAL)
5 PIN MINI-DIN (S-Video)

Optional:

HD15(M) - 5xBNC(F) Interface Cable

Power Source

90-264VAC Universal

Optional:

24VDC @ 2.8A

Power Consumption

50 Watts @115VAC

8 Watts Sleep Mode

Temperature

Operating: 0 to 50°C

Storage: -20 to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 95%NC

Storage: 10 to 95 NC

Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

Dimensions

18.984"(w) x 13.968"(h)

482.19mm x 464.668mm

Depth Behind Panel

3.144" / 108.74mm

Weight

19.0 lbs

Rear Chassis Construction

16 gauge Stainless Steel

Bezel Finish

Black Powder Coat

Cold Rolled Steel

Touch Screen

Optional:

Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

OPTIONS

- Capacitive or Resistive Touch
- HD15 to 5NC adapter cable
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming