



20.1" UXGA Rack Mount Flat Panel



This 20.1" flat panel display is a large screen design to be placed in a variety of Industrial and Process Control environments requiring a rack mount that supports resolutions from VGA to UXGA resolutions*. The display is auto sync compatible with most PC's video standards, and satisfy a wide variety of industrial control and man-machine interface applications where 19" NEMA rack mounting is required.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Anti-Reflective Protective Faceplate
- ◆ Digital, Analog, and NTSC Inputs
- ◆ Picture in Picture
- ◆ Optional Capacitive or Resistive Touch
- ◆ Optional Resident 5BNC

Marks of Conformity:

FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997
Canada: ICES-003
Australia/New Zealand: AS/NZS CISPR 22
CE
RoHS
WEEE



*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

Display Size

20.1 Inch

Panel Type

TFT Active

Resolution

VGA to UXGA*

Pixel Format

640 x 480, 800 x 600, 1024 x 768
1280 x 1024, 1600 x 1200*

Pixel Pitch

.255mm (w) x .255mm (h)

Viewing Angle

Left / Right: 178°/178°
Up / Down: 178°/178°

Active Display Area

16.062" (w) x 12.047" (h)
408.00mm x 306.00mm

Picture in Picture

Small Window: 3.6" (w) x 2.9" (h)
Med Window: 5.0" (w) x 4.9" (h)
Large Window: 6.5" (w) x 5.0" (h)

Contrast Ratio

800:1

Brightness

300 Nits Typical

Colors Supported

16.8M

Backlight

50,000 Hrs Typical

Video Input

0.7Vp-p / 75 ohm Digital

Sync

TTL Separate H&V,
Combined, SOG

Input Connectors

HD15(F), DVI-D Pin, (NTSC / PAL)
5 PIN MINI—DIN (S-Video)

Optional:

HD15(M) - 5xBNC(F) Interface Cable

Power Source

90-264VAC Universal

Optional:

24VDC @ 2.8A

Power Consumption

50 Watts @115VAC
8 Watts Sleep Mode

Temperature

Operating: 0 to 50°C
Storage: -20 to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 95%NC
Storage: 10 to 95 NC

Altitude

Operating: up to 10,000 ft
Storage: up to 40,000 ft

Dimensions

18.984" (w) x 13.968" (h)
482.19mm x 464.668mm

Depth Behind Panel

3.144" / 108.74mm

Weight

19.0 lbs

Rear Chassis Construction

16 gauge Stainless Steel

Bezel Finish

Black Powder Coat
Cold Rolled Steel

Touch Screen

Optional:

Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

OPTIONS

- Capacitive Touch
- Resistive Touch
- HD15 to 5NC adapter cable
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming