



20.1" UXGA NEMA 1 Wall/Arm Mount Display



This 20.1" flat wall/arm display is a compact design to be placed in a variety of industrial and process control environments requiring a large NEMA 1 monitor with resolutions from VGA to UXGA*. These displays are auto sync compatible with PC's video standards and satisfy a wide variety of industrial control and man-machine interface applications and are available in a variety of sizes.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ HD15(F), DVI-D Pin, RCA, Mini Din
- ◆ Compact Low Profile
- ◆ Picture in Picture
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Touch Systems
- ◆ 1600 x 1200 Max Resolution

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

Display Size

20.1 Inch

Panel Type

TFT Active

Resolution

VGA to UXGA*

Pixel Format

640 x 480, 800 x 600, 1024 x 768
1280 x 1024, 1600 x 1200*

Pixel Pitch

.255mm (w) x .255mm (h)

Viewing Angle

Left / Right: 178°/178°
Up / Down: 178°/178°

Active Display Area

16.170"(w) x 12.150"(h)
410.72mm x 308.61mm

Picture in Picture

Small Window: 3.6" (w) x 2.9" (h)
Med Window: 5.0" (w) x 9" (h)
Large Window: 6.5" (w) x 5.0" (h)

Contrast Ratio

800:1

Brightness

300 Nits Typical

Colors Supported

16.8M

Backlight

50,000 Hrs Typical

Video Input

0.7Vp-p / 75 ohm Digital

Sync

TTL Separate H&V,
Combined, SOG

Input Connectors

HD15(F), DVI-D Pin,
(NTSC / PAL)
5 PIN MINI—DIN (S-Video)

Optional:

HD15(M) - 5xBNC(F) Interface Cable

Power Source

90-264VAC Universal

Optional:

24VDC @ 2.8A

Power Consumption

50 Watts @115VAC

8 Watts Sleep Mode

Temperature

Operating: 0 to 50°C

Storage: -20 to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 95%NC

Storage: 10 to 95 NC

Outside Dimension

19.170"(w) x 15.150"(h)

486.92mm(w) x 384.81.4mm(h)

Depth Behind Panel

3.310" / 84.07mm

Weight

24.2 lbs / 11 kg

Bezel Finish

Black Powder Coat

Touch Screen

Optional:

Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

Marks of Conformity:

FCC47 CFR part 15, subpart B

EMC: EN 55022:2006, EN 55024:1998, CISPR

22:2005, CISPR 24:1997

Canada: ICES-003

Australia/New Zealand: AS/NZS CISPR 22

CE

RoHS

WEEE



OPTIONS

- Capacitive or Resistive Touch
- HD15 to 5NC adapter cable
- VBOND Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming