



20" Console Mount Replacement Monitor for Bailey Systems OIS42 & OIS43



The VT20B-CB is a large-screen console mount monitor designed as a direct replacement for Intecolor's Bailey configured monitors (OIS42 and OIS43 systems) 30kHz up to 95kHz. It operates with standard PC-compatible video sources at resolutions from VGA to SXGA. This is a display for replacement in control room and factory floor applications requiring a highly reliable display while offering capabilities for future system upgrades.

FEATURES

- ◆ Auto Sync for systems running 30 to 95kHz
- ◆ .31mm Super-Fine Dot Pitch
- ◆ Digital User Controls
- ◆ 5BNC and HD15(F)
- ◆ Replacement for OIS42 and OIS43
- ◆ Optional Touch Systems

SPECIFICATIONS

Picture Tube

.31mm Dot Pitch
with ARAS coating

Video Bandwidth

135 Mhz dot clock

Resolution Capabilities

VGA to SXGA

Scanning Frequency

Horizontal: 30 to 95kHz
Vertical: 50 to 120Hz

Active Display Area

15.15"(w) x 11.41"(h)
384.81mm x 289.81mm

Rear User Controls

Power, Degauss Digital Membrane User
Controls

Degauss

Automatic on power up and
manual

Video Input Signal

Analog positive .7Vp-p

Sync

Separate or Composite Sync:
TTL pos. or neg.
Sync on Green: 0.3V p-p, neg.

Video Connectors

5BNC and HD15(F)

Power Source

90-264VAC 50/60Hz Universal

Line Frequency

50/60Hz

Power Consumption

130 Watts maximum
30 Watts standby; 15 Watts suspend
mode

Temperature

Operating: 0 to 50C
Non-Operating: -20 to 60C

Relative Humidity

Operating: 5 to 90%NC
Non-operating: 0 to 95%NC

Dimensions

17.65"(w) x 13.94"(h) x 18.31"(d)
448.31mm x 354.08mm x 465.07mm

Weight

56 lbs / 25.5 kg

Agency Approvals

DHHS, FCC A, CE

Warranty

1 Year

Shipping Information

Unit: 50 lbs
Boxed: 62 lbs
Box Size: 24x24x24

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Resistive Touch
- Capacitive Touch