



20" High Resolution Auto Sync Monitor



The VT20B-CF2 is a large 20" industrial monitor designed to operate with standard PC-compatible video sources operating at resolutions from VGA to 1280 x 1024. This is a display for replacement in control room and factory floor applications requiring a high reliability industrial display while offering capabilities for future system upgrades.

FEATURES

- ◆ Auto Sync 30 to 82 kHz
- ◆ .28mm Super-Fine Dot Pitch
- ◆ 5 BNC or HD15(F)
- ◆ Sync On Green Operation
- ◆ Console Mount

SPECIFICATIONS

Picture Tube

.28mm Dot Pitch with
ARAS coating Phosphor: Medium short
(P22)

Video Bandwidth

135 MHz dot clock

Recommended Resolution

VGA to SXGA 1280 x 1024

Scanning Frequency

Horizontal: 30to 82KHz
Vertical: 50 to 120Hz

Active Display Area

14.9" x 10.9"
378.46mm x 276.86mm

Rear User Controls

Power, Degauss, Brightness, Contrast
Geometry

Temperature

Operating: 0° to 50°C
Non-Operating: -20° to 60°C

Relative Humidity

10% to 90%
(non-condensing)

Video Input Signal

Analog Positive 0.7Vp-p (75 ohm)

Sync:

Separate or Composite Sync: TTL pos.
or neg. Sync on Green: 0.3V p-p,
negative

Video Connectors:

5 BNC's or mini 15 pin HD female
connector

Power Source

90-135/180-264 VAC universal @
50/60Hz

Power Consumption

150 Watts maximum
25 Watts standby; 8 Watts suspend
mode

Dimensions

17.50"(w) x 13.75"(h) x 19.87"(d)
444.50mm x 349.25mm x 504.70mm

Weight

55 lbs / 25 kg

Agency Approvals

DHHS, FCC A

Warranty

1 Years

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

www.vartechsystems.com