



21.3" UXGA Transflective Rack Mount LCD



This 21.3" Transflective LCD display is designed to be placed in a variety of applications where the panel will be exposed to indirect sunlight. Transflective displays reflect the light eliminating the need for additional expensive backlights and brightens the screen in indirect sunlight without increasing power consumption. These displays are auto sync compatible with PC's video standards and satisfy a wide variety of industrial control and man-machine interface applications and are available in a variety of sizes.

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ VGA to UXGA Resolution Capabilities*
- ◆ Picture in Picture
- ◆ Anti-Reflective Protective Faceplate
- ◆ HD15(F), DVI-D Pin, RCA, Mini Din
- ◆ Film Enhanced for Indirect Sunlight Readability

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

SPECIFICATIONS

Display Size

21.3"

Panel Type

TFT Active

Resolution Capabilities

VGA to UXGA*

Pixel Format

640x480, 800x600, 1024x768,
1280 x 1024, 1600 x 1200*

Pixel Pitch

.270 mm (w) x .270mm (h)

Viewing Angle

Left / Right: 85°/85°
Up / Down: 85°/85°

Active Display Area

17.008" (w) x 12.756"(h)
432.00mm x 324.00mm

Picture in Picture

Small Window: 3.6" x 2.9"
Medium Window: 5.0" x 4.9"
Large Window: 6.5" x 5.0"

Contrast Ratio

500:1

TouchScreen

Optional:
Capacitive

Brightness

Film Enhanced for Indirect
Sunlight Readability

Backlight

50,000 hrs. Half Life

Colors Displayed

16.7M

Video Input

0.7v p-p, /75 ohm digital

Sync

TTL Separate H&V,
Combined SOG

Input Connectors

HD15(F), DVI-D
RCA, (NTSC/PAL),
5 Pin Mini Din (S-Video)

Optional:

HD15 to 5BNC Adapter
5BNC

Power Source

90-264VAC Universal

Power Consumption

50 Watts @ 115VAC
8 watts sleep mode

Temperature

Operating: 0° to 50°C
Storage: -20° to 60°C

Optional:

Operating: -20° to 55°C

Humidity

Operating: 10 to 95%NC
Storage: 10 to 95%NC

Altitude

Operating: up to 10,000 ft
Storage: up to 40,000 ft

Response Time

T_R = 15ms typical
T_F = 10ms typical

Outside Dimension

22.847" (w) x 18.220"(h)
580.3mm x 488.2mm

Depth Behind Panel

5.525" / 140.3mm

Stud Size & Screw Length

10-32 x 1/2"

Chassis Construction

18 gauge Stainless Steel

Bezel Finish

Black Powder Coated
Cold Rolled Steel

OPTIONS

- Capacitive Touchscreen
- HD15 to 5BNC Cable
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature, -20 to +55C
- Automatic Dimming Sensor
- Manual Full-Range Dimming

www.vartechsystems.com