



Solutions for Demanding Applications

21.3" UXGA NEMA 1 Wall / Arm Mount High Bright



This 21.3" wall / arm mount LCD display is designed to be placed in a variety of Industrial and Process Control environments requiring a large NEMA 1 wall/arm mount that supports resolutions from VGA to 1600 x 1200 resolutions* with HD15 and SOG capabilities. The display is auto sync compatible with most PC's VESA video standards, and is adequate for a wide variety of industrial control and man-machine interface applications.

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ 1600 x 1200 Max. Resolution
- ◆ Picture in Picture
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Resistive Touch Screen
- ◆ HD15(F), DVI-D Pin, RCA, Mini Din
- ◆ Compact Low Profile

*Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

SPECIFICATIONS

Display Size

21.3 Inch

Panel Type

TFT Active

Resolution Capabilities

VGA to UXGA*

Pixel Format

640x480, 800x600, 1024x768,
1280 x 1024, 1600 x 1200*

Pixel Pitch

.270 mm (w) x .270mm (h)

Viewing Angle

L / R: 85°/85° Up / Down: 85°/85°

Active Display Area

17.008" (w) x 12.756" (h)
432.00mm x 324.00mm

Picture in Picture

Small Window: 3.6" (w) x 2.9" (h)
Med. Window: 5.0 (w)" x 4.9" (h)
Large Window: 6.5 "(w)" x 5.0" (h)

Contrast Ratio

500:1

Brightness

750 Nits Typical

Backlight

50,000 hrs. Typical

Colors Displayed

16.8M

Video Input

0.7v p-p, /75 ohm digital

Sync

TTL Separate H&V,
Combined SOG

Input Connectors

HD15(F), DVI-D, RCA, (NTSC/PAL),
5 Pin Mini Din (S-Video)

Optional:

HD15 to 5BNC Adapter
5BNC

Power Source

90-264VAC Universal

Power Consumption

50 Watts @ 115VAC

8 watts sleep mode

Temperature

Operating: -10° to 50°C

Storage: -20° to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 95%NC

Storage: 10 to 95%NC

Altitude

Operating: up to 10,000 ft

Storage: up to 40,000 ft

Outside Dimension

20.00" (w) x 16.75" (h)

508mm x 425.7mm

Depth Behind Panel

3.935" / 99.9mm

Bezel Finish

Black Powder Coat Aluminum

Touchscreen

Optional:

Resistive

Touch Interface

Serial (Optional USB)

Weight

26 lbs/ 11.82 kg

Marks of Conformity:

FCC47 CFR part 15, subpart B

EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997

Canada: ICES-003

Australia/New Zealand: AS/NZS CISPR 22

CE

RoHS

WEEE



OPTIONS

- Resistive Touch
- HD15 to 5BNC Cable
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming