



Solutions for Demanding Applications

32.0" WXGA Tabletop Mount Rugged LCD

This 32" tabletop mount flat panel display is designed to be placed in a variety of public information, industrial and process control environments requiring a large tabletop display that supports resolutions from VGA to 1366 x 768 resolutions. This rugged display is auto sync compatible with most PC's video standards, and can be integrated into a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

Display Size

32.0 Inch

Panel Type

TFT Active

Resolution Capabilities

1366X768

VGA to WXGA

Pixel Format

640x480, 800x600, 1024x768,

1280 x 1024,1366x768*

Input Resolution

1360 x 768 @ 60HZ (Analog & Digital)

Frequency

Horizontal: 30K to 65KHz

Vertical: 56 ~ 75Hz

DDC

DDC 2B

OSD Control

RS232C, Push Button,

IR Remote Controller

OSD Language

English, Chinese

Viewing Angle

H:176° / V:176°

Contrast Ratio

3000:1

Brightness

480 Nits Typical

Colors Supported

16.7 M

Input Connectors

HDMI 1.3c x 2 / VGA, optional HD-SDi/

SDi

Communication Port

D-Sub 9 Pin In, RJ45 In/Out (RS232C In,

RS-485 In/Out)

Power Supply

AC 100 V ~ 240 V (50/60 Hz)

Power Consumption

≤230W (max) Normal Operation

Temperature

Operating: 0° to 35°C

Storage: -20° to 60°C

Humidity

Operating: 85%RH

Storage: 85%RH

Response Time

6.5ms(GTG)

Multimedia

PIP, PBP, Zoom

Fanless Design

Yes

Source Auto Detect

Yes

Speaker

4Ω / 10Wx2 (with Advanced Version only)

Dimensions (w/o stand)

791.2 x 492.2 x 120 mm /

31.15" x 19.38" x 4.72"

Wall / Arm Mount Type

200mm X 200mm VESA

Weight

15 kg / 33.07 lb; Gross 18.5 kg /

40.79 lbs

Warranty

1 year



FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Rugged Metal Enclosure
- ◆ 1366 x 768 Max. Resolution
- ◆ Digital or Analog Interface
- ◆ Wide Viewing Angles
- ◆ 450 nits Brightness
- ◆ Multiple Video Input Selections
- ◆ Aspect Ratio: 16:9

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Advanced Version - Add DVI-D, PC Audio In, IR Extender, Audio Amplifier(speaker ready), Component with Audio In, S-Video/ Video with Audio In
- VBOND Optical bonding for sunlight readability
- HD-SDi / SDi - In x 2, Out x 1 (with Advanced Version only)
- Speaker - 4Ω / 10Wx2 (with Advanced Version only)
- Touch - Optical Touch
- Protective Surface - Tempered Glass
- Metal Stand, IPC Cover (I/O cover,R cover)