



Solutions for Demanding Applications

## 32.0" WXGA VESA / Wall Mount Rugged LCD

This 32" VESA mount flat panel display is designed to be placed in a variety of public information, industrial and process control environments requiring a large tabletop display that supports resolutions from VGA to 1366 x 768 resolutions. This rugged display is auto sync compatible with most PC's video standards, and can be integrated into a wide variety of industrial control and man-machine interface applications.

### SPECIFICATIONS

**Display Size**

32.0 Inch

**Panel Type**

TFT Active

**Resolution Capabilities**

1366 X 768

VGA to WXGA

**Pixel Format**

640x480, 800x600, 1024x768,

1280 x 1024, 1366 x 768\*

**Input Resolution**

1366 x 768 @ 60HZ (Analog & Digital)

**Frequency**

Horizontal: 30K to 65KHz

Vertical: 56 ~ 75Hz

**DDC**

DDC 2B

**OSD Control**

RS232C, Push Button,

IR Remote Controller

**OSD Language**

English, Chinese

**Viewing Angle**

H:176° / V:176°

**Contrast Ratio**

3000:1

**Brightness**

480 Nits Typical

**Colors Supported**

16.7 M

**Input Connectors**

HDMI 1.3c x 2 / VGA, optional HD-SDi/

SDi

**Communication Port**

D-Sub 9 Pin In, RJ45 In/Out (RS232C In,

RS-485 In/Out)

**Power Supply**

AC 100 V ~ 240 V (50/60 Hz)

**Power Consumption**

≤230W (max) Normal Operation

≤12W Suspend/Standby

**Temperature**

Operating: 0° to 35°C

Storage: -20° to 60°C

**Humidity**

Operating: 85%RH

Storage: 85%RH

**Response Time**

6.5ms(GTG)

**Multimedia**

PIP, PBP, Zoom

**Fanless Design**

Yes

**Source Auto Detect**

Yes

**Speaker**

4Ω / 10Wx2 (with Advanced Version only)

**Dimensions (Actual)**

791.2 x 492.2 x 120 mm /

31.15" x 19.38" x 4.72"

**Wall / Arm Mount Type**

200mm X 200mm VESA

**Weight**

15 kg / 33.07 lb

**Warranty**

1 year



### FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ Rugged Metal Enclosure
- ◆ 1366 x 768 Max. Resolution
- ◆ Digital or Analog Interface
- ◆ Wide Viewing Angles
- ◆ 480 nits Brightness
- ◆ Multiple Video Input Selections
- ◆ Aspect Ratio: 16:9

### CONTACT

**HEADQUARTERS**

11529 Sun Belt Ct.  
Baton Rouge, Louisiana 70809

**Phone** 800.223.8050

**International**

001.225.298.0300

**Fax** 225.297.2440

**E-mail**

sales@vartechsystems.com

**Website**

www.vartechsystems.com

### OPTIONS

- Advanced Version - Add DVI-D, PC Audio In, IR Extender, Audio Amplifier (speaker ready), Component with Audio In, S-Video/ Video with Audio In
- VBOND Optical bonding for sunlight readability
- HD-SDi / SDi - In x 2, Out x 1 (with Advanced Version only)
- Speaker - 4Ω / 10Wx2 (with Advanced Version only)
- Touch - Optical Touch
- Protective Surface - Tempered Glass
- Metal Stand, IPC Cover (I/O cover, R cover)