



52.0" VBOND 1080p High Def Tabletop Rugged LCD

VarTech Systems unique VBOND process seals either a top cover glass or touch screen directly to the face of the display bezel. This bonding process eliminates the air-gap between the display and the cover glass, vastly reducing reflective light, which causes visual washout of the display image. VBOND also enhances structural integrity by supporting the LCD assembly with the cover glass. The bond maintains perfect display uniformity while providing shock protection and elimination of fogging caused by trapped moisture accumulating in typical air gap assemblies.

FEATURES

- ◆ Sunlight Readable VBOND enhanced LCD screen
- ◆ Bright Active Matrix TFT Display
- ◆ Digital or Analog Interface
- ◆ Wide Viewing Angles
- ◆ 500 nits Brightness
- ◆ Multiple Video Input Selections
- ◆ Aspect Ratio: 16:9
- ◆ PIP, PAP, Zoom
- ◆ Fanless Design
- ◆ Source Auto Detect

SPECIFICATIONS

Display Size

52.0 Inch

Panel Type

TFT Active

Resolution

1920 x 1080 pixels

Input Resolution

1920 x 1080 @ 60HZ (Analog and Digital)

Frequency

Horizontal: 30K to 90KHz
Vertical: 56 ~ 75Hz

DDC

DDC 2B

OSD Control

RS232C, Push button,
IR Remote Controller

OSD Language

English, Japanese, Chinese

Viewing Angle

Horizontal: 176°
Vertical: 176°

Contrast Ratio

1500:1 Typical

Brightness

500 Nits Typical

Colors Supported

16.7 M

Input Connectors

DVI, VGA, S-Video,
Component, AV

Optional: HD-SDi BNC and /or Audio

Communication Port

D-Sub 9 Pin, RJ145 In/Out
(Transport Protocol - RS-232, RS-485 I/O)

Power Source

100-240 VAC (50/60Hz) Universal

Temperature

Operating: 5° to 40°C
Storage: -20° to 60°C

Humidity

Operating: 85%RH
Storage: 85%RH

Response Time

6.5ms (GTG)

Dimensions with Stand

1269mm x 819mm x 299.15mm (WxHxD)

VESA Mount

200mm x 200mm / 200mm x 600mm

Multimedia

PIP, PAP, Zoom

Fanless Design

Yes

Source Auto Detect

Yes

Warranty

2 year

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Protective Surface - 4mm (AG/AR), Tempered Glass
- Table Stand
- Conformal coating to all internal system circuit boards
- -20°C Operational Temperature
- Audio Amplifier - In *1 , Out *1
- HD-SDI / SDi - In *1 , Out *1

www.vartechsystems.com