



VTPC150PSS NEMA 4X Panel Mount Computer

Panel PC computer's are an ideal HMI solution complete with standard resistive touch and a multitude of I/O ports. These small footprint all-in-one computers are ideal in a variety of harsh environment manufacturing facilities.

SPECIFICATIONS

Display

15" XGA TFT LCD

Resolution

1024 x 768

Viewing Angle

130° (H) / 100° (V)

Pixel Pitch

0.297mm

Display Colors

16.2M

Brightness

400 cd/m² (Optional VBOND)

Contrast Ratio

600:1

Response Time

12 ms

Processor

2.16 GHz Intel Dual Core T3400 with a 667 MHz FSB

BIOS

Phoenix-Award 16Mbit (SPI) with RPL/PXE LAN Boot ROM, SmartView and customer CMOS backup

O/S

Microsoft XP Professional (optional Windows XP Embedded SP2 or Windows 7)

System Memory

2 DDR2 533/667 SDRAM sockets, 2GB standard, 4GB optional (~3.25 recognizable)

Chip Set

Intel® GME965+ICH8M/EM

VGA

Intel® GME965 GMCH Gen4 integrated graphics engine

Hard Drive

320GB Fast Access SATA drive

Power Input

90-240V AC

Optional:

6 to 32V DC

I/O Ports

3 RS-232 COM port

(Optional RS-422\485 port)

2 LAN ports

4 USB 2.0

2 Audio jacks

Firewire Ports

2 x IEEE 1394a

DVD Drive (SATA) (Optional)

DVD-R, DVD+R, DVD-RW, DVD+RW,

DVD-R DL, DVD+R9, CD-R, CD-RW

Temperature

Operational: 0° to 60°C (optional -20°)

Storage: -40° to 65°C

Humidity

Operational: 10 to 90% RH NC

Storage: 5 to 95% RH NC

Touch Screen

Resistive Standard

Touch Screen Interface

USB

Bezel Construction

NEMA 4X (IP66) 316 - Stainless Steel,

Gasketed

Weight

17.12 lb



FEATURES

- ◆ Resistive Touch Screen
- ◆ Powerful 2.16 GHz Intel Dual Core Processor
- ◆ 316-stainless steel front bezel
- ◆ Intel® GME965 GMCH Gen4 integrated graphics engine
- ◆ Rugged Aluminum Chassis
- ◆ High-Performance Fast Access Disk Drive
- ◆ WINDOWS XP OS

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Hard Drive expandable
- PCI Expansion 1 to 3 slots
- PCI express x16 expansion slot
- RS-422\485 port
- 6 to 32V DC
- DVD Drive (SATA) - DVD-R, DVD+R, DVD-RW, DVD+RW, DVD-R DL, DVD+R9, CD-R, CD-RW
- VBOND Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- -20°C Operational Temperature
- Solid state SATA hard drive
- PCI express x16 expansion slot
- Wireless Connection
- Sunlight Readable Technology
- Windows XP Embedded SP2 or Windows 7

Specs subject to change without notice. Please inquire before ordering.

www.vartechsystems.com