

VTPC170V

ISO
9001:2008
REGISTERED



VARTECH
SYSTEMS INC.

Solutions for Demanding Applications

VTPC170V NEMA 4 (IP65) Fully Enclosed LCD & Computer

VarTech's multi-functional, user friendly, industrial grade VESA mount 17" NEMA 4 (IP65) fully enclosed touch screen computer offers extensive features, is housed in a gasket sealed black powder coated enclosure, is incorporated with a 380 nit (cd/m²) bright active matrix TFT display and is integrated with Intel's Atom N270 1.6GHz Processing Technology. The system has no external vents, so nothing can get under its skin; including weather, dust, dirt, moisture, oil, chemicals or other harsh contaminants. With its lightweight yet rugged construction and either pre-cabled or bulkhead connectors, these models are easily mounted on walls, stands, arms or other industrial equipment. With optional brackets, it conforms to VESA mounting standards.

FEATURES

- 17" Bright Active Matrix TFT Display, 380 nits (cd/m²)
- Powered by Intel Atom N270 1.6GHz Processor
- 2 GB 200-pin SO-DIMM DDR 333/400MHz
- 320 GB SATA Fast Access Disk Drive Standard (Up to 1TB Available)
- Fully-Enclosed, Gasket Sealed NEMA 4 (IP65) Black Powder Coated Enclosure
- Resistive Touch Screen Standard (other technologies available)
- Windows XP Professional Operating System (optional Windows Embedded or Windows 7)
- High Contrast Ratio & Definition, Outstanding Vivid Color & Image Quality
- Wide Color Gamut
- 16.8 million colors
- Energy Efficient, Low Power Consumption
- High Environmental Performance and Reliability
- Anti-Reflective Protective Window
- SXGA (1280 x 1024) Resolution
- Wide Operational Temperature Range, -10°C to +55°C (14°F to +131°F)(optional extended temperature ranges available)
- RoHS Compliant
- Engineered and Manufactured by VarTech Systems, an ISO 9001 Registered Company
- **Engineered, Fabricated and Assembled in the USA**
- Two (2) Year Warranty

SPECIFICATIONS

Display

17" SXGA TFT LCD

Resolution

1280 x 1024

Viewing Angle

160° (H) / 165° (V)

Pixel Pitch

0.264mm

Display Colors

16.7M

Brightness

380 cd/m²

Contrast Ratio

1000:1

Response Time

5 ms

Power Input

100-240 VAC 1.5A 50/60 Hz

Optional:

9-36V DC,

Power Consumption

45W

Processor

Intel® Atom™ N270, 1.6 GHz Processor with a 533 Mhz FSB

Optional Processor:

T4500 2.30 GHz 800MHz FSB

Pentium Dual Core CPU

BIOS

AMI BIOS

O/S

Microsoft XP Professional (optional Windows Embedded Standard to Windows 7)

System Memory

2GB DDR2 533 SO-DIMM

Hard Drive

320GB Fast Access SATA

VGA

Intel Generation 3.5 integrated GFX Core (133Mhz)

Sealed I/O

1 Power Connector

1 LAN port (2 LAN Optional)

2 RS-232 COM port

3 USB 2.0 ports

I/O with optional Dual Core CPU:

3 USB, 2 Serial, 1 LAN connector

LAN

PCIe Realtek 8111CP GbE

Connections

Sealed connections for USB, Serial, Ethernet, and Power

Temperature

Operational: -10° to 60°C (14 to 140F)

Storage: -20° to 65°C (-4 to 149F)

Humidity

Operational: 0 to 90% RH NC

Storage: 5 to 95% RH NC

Touch Screen

Resistive

Display Construction

NEMA 4 (IP65) - Black Powder Coat

Dimensions:

17.26" (W) x 17.59" (H) x 5.21" (D)

Height is 13.72" when not allowing for connections at bottom/24lbs.

Approximate Shipping Dimensions and Weight

24" x 21" x 10" (WxLxH) / 29lbs.

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- T4500 2.30 GHz 800MHz FSB Intel Dual Core Processor (operating temperature with dual core processor: -10° to 45°C / 14° to 113°F)
- Optional 4GB DDR2 PC2-5300 SO-DIMM System Memory (only in conjunction with the Dual Core processor)
- Solid State SATA hard drive
- Up to 1TB Hard Drive Available
- Can Support Dual Hard Drives
- CANbus
- Windows Embedded Standard or Windows 7
- Alternate Touch Screen Technologies: Capacitive

Marks of Conformity:

Product Safety: UL60950-1/CSA C22.2 No. 60590-1 (2006/95/EC, EN 60950-1:2006, IEC 60950-1:2005) FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997
Canada: ICES-003
Australia/New Zealand: AS/NZS CISPR 22

CE

RoHS

WEEE



or Armor Touch

- Wireless Connection
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity (VBOND)
- Fan-less Design (will require a thermal dissipation heat-sink on rear of enclosure)
- Optional Operating: -20°C (-4°F) to 60°C (140F)
- 6 to 32V DC Power Supply
- For Rear Exiting connectors please see VTPC170VR
- * Available with adjustable tilt pedestal