



Picture  
Coming  
Soon

**19" Purged Enclosed Computer for Class 1 Div 1 Environments**

The VT950ESC is a NEMA 4X HMI system designed to meet Class 1, Div 1 protection. The purge system uses an automatic pressure switch to automatically trigger alarms in case of pressure loss.

**Durable**

The VT950ESC can easily handle the punishment of harsh computing environments. They are proven tough in real world applications such as industrial production areas, outdoor kiosks and public terminals.

The VT950ESC chassis has no external vents, so nothing can get under its skin, including dust, dirt, moisture, oil, chemicals or other harsh contaminants.

A hard-anodized aluminum heat exchanger and internal heat management system keep it cool in environments where ambient temperatures approach 50°C -- without using outside air.

**Easy Access**

VT950ESC are designed with easy maintenance and up-grades in mind. A latched panel provides simple access to this NEMA 4X HMI system. With its moderate weight and dimensions, VT950ESC enables flexible mounting options.

**FEATURES**

- ◆ Designed to Meet Class 1 Division 1
- ◆ Purged pressure switch
- ◆ NEMA 4x sealed enclosure
- ◆ Water proof and dust proof
- ◆ Stainless steel construction
- ◆ Easy latch access
- ◆ Hard-anodized aluminum heat sink
- ◆ Closed loop thermal cooling for high heat environments
- ◆ Medium footprint
- ◆ Flexible mounting options
- ◆ Keyboard/mouse optional
- ◆ LCD screen shielded by a Tempered Glass Protective Overlay

\*Supports all VESA standard video formats

**CONTACT**
**HEADQUARTERS**

11529 Sun Belt Ct.  
Baton Rouge, Louisiana 70809

**Phone** 800.223.8050

**International**

001.225.298.0300

**Fax** 225.297.2440

**E-mail**

sales@vartechsystems.com

**Website**

www.vartechsystems.com

**SPECIFICATIONS**
**Display**

19", 1280 x 1024 SXGA, LCD screen shielded by a Tempered Glass Protective Overlay

**Processor**

1.73GHz Intel Pentium Core Duo (Dual-Core) Mobile Processor T2080

**BIOS**

Award PnP 4MB Flash ROM BIOS

**O/S**

Windows XP Professional (optional Windows XP Embedded)

**System Memory**

SO-DIMM DDRII 667/533/400 2 GB

**Graphics**

Integrated VGA Engine in chipset (Intel GMA 950)

**LAN**

Integrated Intel Gigabit PCI Express LAN Chip

**Hard Drive**

320 GB Fast Access Disk Drive

**Power Input**

100-240VAC 1.5A 50/60 HZ

**Power Connector**

Standard Power Inlet (IEC320 C14)

**Dimensions**

20" W x 18" D x 11" H

**Expansion Slots**

Mini PCI x 1

**DVD Drive (E-IDE / ATAPI)**

DVD-R, DVD+R, DVD-RW, DVD+RW, DVD-R DL, DVD+R9, CD-R, CD-RW

**I/O Ports**

1 Realtek ALC882 HD Audio CODEC  
 PS/2 Keyboard Connector x 1  
 PS/2 Mouse Connector x 1  
 AC Adapter Connector x 1  
 DVI Port x 1  
 S-Video Out Port x 1  
 COM Port x 1  
 USB 2.0 Port x 4  
 1394 Port x 1  
 RJ45 LAN Port x 1  
 Line In / SPDIF In x 1  
 Speaker Out x 1  
 MIC In x 1  
 Center / Subwoofer x 1  
 Rear Surround / SPDIF Out x 1  
 Side Surround x 1

**Temperature**

Operational: 5° - 55°C

**Construction**

316 stainless steel  
 Anodized aluminum heat sink  
 10" handles  
 IP67 - NEMA 4X, waterproof and dustproof  
*Enclosure Only:*  
 18" H x 20" W x 11" D, 66 lb  
*Purge System Only:*  
 20" (H) x 11" (W) x 10.5" (D), 38 lb

**OPTIONS**

- Purge System Mounting to Side (L/R), Top or Bottom
- Windows XP Embedded

**\*\*Purge System w/Pressure Switch Next Page\*\***

**www.vartechsystems.com**



**Purge System w/  
Pressure Switch**

This Rapid Exchange® purging system operates on a supply of compressed instrument air or inert gas. It regulates and monitors pressure within sealed (protected) enclosure(s), in order to prevent combustible dust accumulation or remove and prevent flammable gas or vapor accumulations. The system accomplishes four air exchanges and maintains a "safe" (0.25") pressure. The system includes an Electrical Power Control Unit (EPCU) that monitors system operation and controls enclosure power. All start-up requirements must be satisfied before the EPCU will energize power to the enclosure(s). These processes reduce the hazardous (classified) area rating within the enclosure(s), in accordance with the NEC - NFPA 70, Article 500, NFPA 496 and ISA 12.4.

## MATERIAL SPEC

### Regulator Body

Zinc w/ Enamel Finish

### Regulator Handle

Polycarbonate

### Enclosure Pressure Gauge

Alum. w/ Enamel Finish

### Tube Fittings

316 SS Forged Body

### Tubing

316 SS 1/4" .035 Welded

### System Nameplates

Silk screened Lexan® & SS

### Fastener Hardware

SS Screws & Bolts

### Mounting Plate

316 14 Ga #3 Brush SS

### EPCU Enclosed Body

Bead Blast Cast Alum.

### Enclosure Warning

### Nameplate

Silkscreened SS

Lexan® is a registered trademark of the General Electric Company.

## Specifications

### Weight

38lb

### Temp. Range

-20F to 120F

### Supply Pressure Range

5 - 120 psi

### Supply requirements

Clean air or inert gas

### Safe Pressure Setpoint

.25" / 1.0"

### Safe Pressure Flow Rate

0.1 - 3.5 SCFH - Enclosure integrity determines actual flow rate

### Safe Pressure Flow Rate

4 SCFM / 240 SCFH - With regulator set to 60 psi min. during exchange

### Exchange Time

As required - Time required to exchange 4 volumes within the enclosure(s), based on actual measured safe pressure flow rate or 5 minutes, whichever is greater

### System Supply Port

1/4" tube fitting

### Enclosure Supply Fitting

1/4" tube fitting

### Enclosure Reference Fitting

1/4" tube fitting

### EPCU Conduit Port Size

1/2" FPT

### EPCU Power Requirements

120 VAC 60Hz 10

### EPCU Power Consumption

500mA

### Dimensions

20" (H) x 11" (W) x 10.5" (D)  
Height & Width dimensions reflect mounting plate measurements. Depth dimensions reflects overall measurement of system, including components.

### Mounting

Side (L/R), Top or Bottom

## OPERATION

In accordance with system instructions, start-up requires air supply to be engaged and EPCU power to be energized. The system must perform an exchange cycle (determined by the safe pressure flow rate — 5 minutes minimum) before power can be energized. Loss of safe pressure causes the EPCU to deenergize power to the protected enclosure(s). The purge system includes an explosion proof differential pressure switch with form "C" contacts for audible or visual alarm systems.

[www.vartechsystems.com](http://www.vartechsystems.com)  
Email: [sales@vartechsystems.com](mailto:sales@vartechsystems.com)  
Toll Free: 800.223.8050

